

## Basic System Configuration

- Pre-loaded, tested, and fully integrated OmniEngine Enterprise software
- Microsoft Windows Server 2008 R2 or Linux
- Available with 8TB/16TB SATA Storage
- Optional SAN
- Supports up to 4 OmniAdapters on Linux and up to 2 OmniAdapters on Windows

## Hardware Options Available on Omnipliance

### OmniAdapter 1G

The OmniAdapter 1G is a high performance network analyzer card that supports up to 2 full-duplex or 4 half-duplex connections providing advanced monitoring and troubleshooting of Gigabit networks.

OmniAdapter 1G is a four-port, PCI Express network analyzer card available in the following configurations:

- Four SFP cages
- Four fixed RJ45 ports (10/100/1000)
- Two SFP cages and two RJ45 ports (1000)

OmniAdapters 1G are supported on both Windows and Linux operating systems.

### OmniAdapter 10G

WildPackets' OmniAdapter 10G is a high performance, PCI Express, full-duplex 10 Gigabit network analyzer card with 2x10 Gbps optical interfaces that has been optimized for monitoring and troubleshooting traffic on 10 Gigabit Ethernet networks. The two-port, OmniAdapter 10G provides hardware-accelerated packet tracing and dynamically configurable filtering together with high precision timestamping. The network adapter is available with 1x850nm MFF XFP or 1x1310nm SMF XFP optical

transceivers with LC connectors.

OmniAdapters 10G are supported on both Windows and Linux operating systems.

## Error Packet Capture

OmniAdapter network analyzer cards have the ability to capture error packets on the network. These errors include: Runt, Oversize, Frame Alignment, and CRC Errors. To capture errors on Gigabit and 10 Gigabit segments, you must use a WildPackets OmniAdapter.

## Other Supported Gigabit and 10Gigabit Network Adapters

- Intel<sup>®</sup> PRO/1000 Quad Port Server Adapter
- Intel<sup>®</sup> PRO/10GbE Dual Port Server Adapter

## Supported Networks

The Omnipliance Core analyzes traffic on Ethernet, Fast Ethernet, full-duplex Gigabit and 10 Gigabit networks.

## Bus

- Four PCI Express 2.0 x8 Slots

## Environmental

- Operating Temperature: 10° to 35° C (50° to 95° F)
- Non-operating Temperature: -40° to 70° C (-40° to 158° F)
- Operating Relative Humidity: 8% to 90% (non condensing)
- Non-operating Relative Humidity: 5% to 95% (non condensing)
- 1942.10 BTU/Hour

## Power Requirement

- 800W redundant power supply

## Supported Operating System and Browser

- Microsoft Windows Server 2008 R2 or Linux

## System Input Requirements

- AC Input Voltage: 100-240 VAC
- Rated Input Current: 100 (11A) - 240V (5A)
- Rated Input Frequency: 50-60 Hz

## Omnipliance Warranty

- On-site warranty service
- Available with one or three year warranty