

WildPackets® TimeLine™ Network Recorder

Technical Specifications

Basic System Configuration

- Pre-loaded, tested, and fully integrated OmniEngine Enterprise software
- 3 OmniPeek Connect Analyzers
- Linux
- 3U server chassis
- Available with 8TB, 16TB, or 32TB Storage
- Supports up to 4 OmniAdapters

Hardware Options Available on TimeLine

OmniAdapter 1G

The OmniAdapter 1G is a high performance network analyzer card that supports up to 2 full-duplex or 4 half-duplex connections providing advanced monitoring and troubleshooting of Gigabit networks.

OmniAdapter 1G is a four-port, PCI Express network analyzer card available in the following configurations:

- Four SFP cages
- Four fixed RJ45 ports (10/100/1000)
- Two SFP cages and two RJ45 ports (1000)

OmniAdapter 10G

WildPackets' OmniAdapter 10G is a high performance, PCI Express, full-duplex 10 Gigabit network analyzer card with 2x10 Gbps optical interfaces that has been optimized for monitoring and troubleshooting traffic on 10 Gigabit Ethernet networks.

The two-port, OmniAdapter 10G provides hardware-accelerated packet tracing and dynamically configurable filtering together with high precision timestamping. The network adapter is available with 1x850nm MFF XFP or 1x1310nm SMF XFP optical transceivers with LC connectors.

Error Packet Capture

OmniAdapter network analyzer cards have the ability to capture error packets on the network. These errors include: Runt, Oversize, Frame Alignment, and CRC Errors. To capture errors on Gigabit and 10 Gigabit segments, you must use a

WildPackets OmniAdapter.

Other Supported Gigabit and 10Gigabit Network Adapters

- Intel® PRO/1000 Quad Port Server Adapter
- Intel® PRO/10GbE Dual Port Server Adapter

Supported Networks

The TimeLine network recorder analyzes traffic on Ethernet, Fast Ethernet, full-duplex Gigabit and 10 Gigabit Ethernet networks.

Bus

- Four PCI Express 2.0 x8 slots

Environmental

- Operating Temperature: 10° to 35° C (50° to 95° F)
- Non operating Temperature: -40° to 70° C (-40° to 158° F)
- Operating Relative Humidity: 8% to 90% (non condensing)
- Non-operating Relative Humidity: 5% to 95% (non condensing)
- 2782.25 BTU/Hour

Power Requirement

- 800W redundant power supply

System Input Requirements

- AC Input Voltage: 100-240 VAC
- Rated Input Current: 100 (10A) - 240V (4A)
- Rated Input Frequency: 50-60 Hz

Supported Operating System

- Linux

Omnipliance Warranty

- On-site warranty service
- Available with one or three year warranty



1340 Treat Blvd, Suite 500
Walnut Creek, CA 94597
main (925)937-3200
fax (925)937-3211

www.wildpackets.com